

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

- B¹
- threads sized and shaped to be threadably mated with the threaded surfaces of the implant arms;
- b) a break-off driving head having a first cross section associated therewith perpendicular to the axis of rotation; said driving head adapted to rotate and torque said body in said implant until a preselected torque occurs at which time said break-off head breaks from said body; and
- c) a removal head external of said body and having a polyhedral shape with radially outward facing engagement surfaces adapted to engage a removal tool; said removal head located between said driving head and said body; said removal head having a second cross section associated therewith perpendicular to the axis of rotation with said second cross section being different from said first cross section.

B²

5. A medical implant system comprising:

- a) an open headed medical implant having a head formed by a pair of spaced interiorly threaded arms defining a channel therebetween sized and shaped to receive a rod member; and;

- B²
- b) a closure member including:
 - i) a body having an axis of rotation and a threaded cylindrical shaped radially outward surface with threads sized and shaped to be threadably mated with said threaded arms;
 - ii) a driving head having a first cross section associated therewith perpendicular to the axis of rotation; said driving head operably allowing a user to rotate and torque said body until a preselected torque occurs whereat said driving head breaks from said body; and
 - iii) a removal head located external of said body and between said body and said driving head; said removal head having a radially outward facing surface sized and shaped to engage a removal tool; said removal head having a second cross section associated therewith perpendicular to the axis of rotation with said second cross section being different in comparison to said first cross section.

B³ 9. A closure for use in conjunction with an open headed

medical implant having a pair of interiorly threaded arms forming a channel therebetween for receiving the closure; said closure closing said channel upon being received between said arms; said closure comprising:

- B3
- a) a cylindrical shaped body with a radial outward threaded surface sized and shaped to be threadably received between the arms of the implant; said body having an axis of rotation;
 - b) a driving head axially aligned with and attached to said body and having a first gripable outer surface; said driving head operably rotating and torquing said body and breaking from said body at a preselected torque; and
 - c) a removal head axially aligned with and attached to said body for removing said body from the implant; said removal head being located external of said body and between said body and said driving head; said removal head having a second gripable radially outward facing outer surface; said first and second gripable outer surface being different in configuration so as to prevent a tool used with said first surface from also accidentally gripping said second surface.

The following are the amended claims noted above in a marked format indicating additions by underlining and deletions by bracketing:

1. (Twice Amended) A closure for use in conjunction with a medical implant that is sized and shaped to operably close a channel between two spaced arms with each of said arms having an inward threaded surface; said closure comprising:
 - a) a body having an axis of rotation and a threaded cylindrical shaped radially outward surface with threads sized and shaped to be threadably mated with the threaded surfaces of the implant arms;
 - b) a break-off driving head having a first cross section associated therewith perpendicular to the axis of rotation; said driving head adapted to rotate and torque said body in said implant until a preselected torque occurs at which time said break-off head breaks from said body; and
 - c) a removal head external of said body and having a polyhedral shape with radially outward facing engagement surfaces adapted to engage a removal tool;
said removal head located between said driving head

and said body; said removal head having a second cross section associated therewith perpendicular to the axis of rotation with said second cross section being different from said first cross section.

5. (Twice Amended) A medical implant system comprising:

- a) an open headed medical implant having a head formed by a pair of spaced interiorly threaded arms defining a channel therebetween sized and shaped to receive a rod member; and;
- b) a closure member including:
 - i) a body having an axis of rotation and a threaded cylindrical shaped radially outward surface with threads sized and shaped to be threadably mated with said threaded arms;
 - ii) a driving head having a first cross section associated therewith perpendicular to the axis of rotation; said driving head operably allowing a user to rotate and torque said body until a preselected torque occurs whereat said driving head breaks from said body; and
 - iii) a removal head located external of said body and between said body and said driving head; said removal head having a radially outward facing

surface sized and shaped to engage a removal tool; said removal head having a second cross section associated therewith perpendicular to the axis of rotation with said second cross section being different in comparison to said first cross section.

9. (Twice Amended) A closure for use in conjunction with an open headed medical implant having a pair of interiorly threaded arms forming a channel therebetween for receiving the closure; said closure closing said channel upon being received between said arms; said closure comprising:
- a) a cylindrical shaped body with a radial outward threaded surface sized and shaped to be threadably received between the arms of the implant; said body having an axis of rotation;
 - b) a driving head axially aligned with and attached to said body and having a first gripable outer surface; said driving head operably rotating and torquing said body and breaking from said body at a preselected torque; and
 - c) a removal head axially aligned with and attached to